

TECHNICAL DATA SHEET

HVCRC® 190 - 28

Epsilon Advanced Conductors

EPSILON
CABLE

Governing Units: Metric

STRANDING CONFIGURATION

	No. & Diameter of HVCRC core	1 x 5.97	mm
	Aluminium Layers Construction / height	16 TW x	2.78 mm
	1st layer composition and ϕ_{eq}	6 x	3.92 mm
	2nd layer composition and ϕ_{eq}	10 x	3.86 mm
	Lay Direction of outer layer	Right Hand (Z)	

CONDUCTOR PROPERTIES


Cross Sectional Area - Annealed Aluminium	189.1	mm ²
Cross Sectional Area - HVCRC Core	28.0	mm ²
Total Area of Conductor Cross Section	217.1	mm ²
Nominal equivalent Aluminium Area (1350-H19 at 61%IACS)	195.3	mm ²
Overall Diameter of Conductor	17.09	mm
Mass per unit length - Annealed Aluminium	523.1	kg/km
Mass per unit length - Core	51.8	kg/km
Mass per unit length - Conductor	574.9	kg/km
Ultimate Tensile Strength of Conductor	71.2	kN
Core Rated Tensile Strength	59.8	kN
Coefficient of Linear Expansion Above Thermal Kneepoint	1.6	10 ⁻⁶ K ⁻¹
Coefficient of Linear Expansion Below Thermal Kneepoint	18.04	10 ⁻⁶ K ⁻¹
Final Modulus of Elasticity Above Thermal Kneepoint	112	GPa
Final Modulus of Elasticity Below Thermal Kneepoint	62	GPa

THERMAL SPECIFICATIONS

Maximum Continuous Operating Temperature ⁽²⁾ (surface temperature)	180	°C
Maximum Emergency Temperature / 8760 Hours ⁽²⁾ (surface temperature)	200	°C
Thermal Heat Capacity for Annealed Aluminium Layers	499.6	W.s/m.°C
Thermal Heat Capacity for Composite Core	41.4	W.s/m.°C

ELECTRICAL SPECIFICATIONS

Maximum DC Electrical Resistance at 20°C (1370-O at 63%IACS)	0.1481	Ω.km ⁻¹
Temperature Coefficient of Resistance	4.03	10 ⁻³ K ⁻¹
AC Nominal Resistance at 25°C (surface temperature)	0.1516	Ω.km ⁻¹
AC Nominal Resistance at 75°C (surface temperature)	0.1814	Ω.km ⁻¹
AC Nominal Resistance at 160°C (surface temperature)	0.2320	Ω.km ⁻¹
AC Nominal Resistance at 180°C (surface temperature)	0.2439	Ω.km ⁻¹
AC Nominal Resistance at 200°C (surface temperature)	0.2559	Ω.km ⁻¹
AC Current Rating at 160°C (surface temperature) ⁽¹⁾	892	A
AC Current Rating at 180°C (surface temperature) ⁽¹⁾	946	A
AC Current Rating at 200°C (surface temperature) ⁽¹⁾	997	A



Geometric Mean Radius (GMR)

6.98 mm

Inductive Reactance Ø0.3m radius

0.237 Ω.km⁻¹

Capacitive Reactance Ø0.3m radius

0.205 MΩ.km

(1) Ampacity calculations based on IEEE Standard 738-2012, according to the following data:

25 °C ambient temperature, 0.61 m/s wind velocity with an angle of 90 °,
 1000 W/m² solar radiation, 0.5 solar absorption coefficient,
 0.6 emissivity coefficient, Resistance AC at 50 Hz current frequency.

(2) Temperatures defined according to ASTM B987-20.

Reference standards for core properties: ASTM B987-20.

Reference standards for electrical specifications: IEC 62219.

Reference standards for stranding parameters: ASTM B857-14/IEC 62219.

Depending on conductor manufacturer rated specifications may slightly change.

Revision 04
 Ref. Document ST21-00143
 Date 12-Sep-2023

This document is the property of EPSILON COMPOSITE

contact@epsilon-cable.com
www.epsilon-cable.com